

POLYESTER CONSTRUCTION HARNESS

PRODUCT INFORMATION

This vest style design polyester webbing fall arrest harness is perfect for any general working at height application.

PRODUCT FEATURES

- ⇒ Frontal dee rings for frontal fall arrest when used jointly.
- ⇒ Rear fall arrest dee ring
- ⇒ Vest style design, making it simple to don.
- ⇒ Equipped with a label pack housing all relevant harness information including donning instructions, connection instructions, AS/NZS 1891.1 2007 certification and inspection grid. The label pack is also equipped with an oversized pull-free lanyard ring enabling the user to temporarily park a lanyard.
- ⇒ Fully adjustable chest strap.
- ⇒ Fully adjustable shoulder straps.
- ⇒ Fully adjustable leg straps.
- ⇒ All attachment points are clearly labelled and define the application of the attachment.
- ⇒ Brightly coloured webbing enables the user to be easily identified whilst working at heights.



TECHNICAL INFORMATION

- ⇒ Manufactured from heavy duty and lightweight 43mm polyester webbing.
- ⇒ Weight 1.2 kg

STANDARDS

- ⇒ Certified to Australian and New Zealand Standards AS/NZS 1891.1 - 2007.

APPLICATIONS

- ⇒ Construction & Maintenance
- ⇒ Scaffolding
- ⇒ Warehousing

ORDERING & PACKAGING INFORMATION

Part Number	Description	Attachment Points				Extended Dee	Size	Cat	Min Order	Pack Dimensions L x W x H	Bar Code
		Rear	Frontal	Confined Space	Work Positioning						
M1020063	Polyester webbing Construction Harness	Y	Y	N	N	N	Medium	A	1	360 x 322 x 105	9333633009081

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF PERSONAL PROTECTIVE PRODUCTS AVAILABLE FROM SPERIAN PROTECTION AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. SPERIAN PROTECTION RECOMMENDS ALL USERS OF ANY PERSONAL PROTECTIVE EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY.