

▶ ▶ ▶ MILLER® MINILITE FALL ARRESTOR

PRODUCT INFORMATION

The FL3M MiniLite is a type 2 fall arrest device with a quick activating braking system that limits a free fall to millimeters. This acts to reduce the risk of hitting a lower level surface, and reduce the need for a complicated rescue procedure.

PRODUCT FEATURES

- ⇒ Corrosion resistant interior
- ⇒ Visual load indicator, which notifies the user that the unit has been involved in a fall.
- ⇒ High impact protective outer cover.
- ⇒ Lightweight design
- ⇒ 3mtr webbing
- ⇒ Integral energy absorber.
- ⇒ Compact design to fit into the palm of your hand.

STANDARDS

- ⇒ Fully compliant to AS/NZS 1891.3 as a type 2 fall arrest device.



TECHNICAL INFORMATION

Housing:	Thermoplastic Cover
Webbing:	25.4 X 1.5 MM Sangle Polyester
Snap Hook:	Drop forged Steel
Working Length:	2.6mtrs
Overall Length:	3mtrs
Maximum capacity:	140.6 Kg
Ultimate Strength:.	13.3 kN
Maximum arrest distance:	1.06 m
Maximum arresting force:	4 kN (APPROX.)
Weight:	1.4 Kg

APPLICATIONS

- ⇒ Construction
- ⇒ Maintenance
- ⇒ Elevated Work Platforms
- ⇒ Warehousing

ORDERING & PACKAGING INFORMATION

Part Number	Description	Length	Terminations	Weight	Cat	Min Order	Package Dimensions L x W x H	Bar Code
FL3M	MiniLite Fall Arrestor	3mtrs	Karabiner at top/ swivel	1.4kg	A	1	27 x 17 x 10	612230104870

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF PERSONAL PROTECTIVE PRODUCTS AVAILABLE FROM SPERIAN PROTECTION AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. SPERIAN PROTECTION RECOMMENDS ALL USERS OF ANY PERSONAL PROTECTIVE EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY.