



Model DH-AP-2 includes the following

Item	Part no.	Description
1	DH-AP-2	MILLER DURAHOIST Aluminum Portable Fall-Arrest Anchor Post Extension
accessories shown, but not included		
2	DH-AP-1	MILLER DURAHOIST Portable Fall-Arrest System Anchor Post

DESCRIPTION

The Extension Post is designed for use with MILLER DURAHOIST portable fall-arrest system anchor post to provide a single fall-arrest tie-off point above the swivel tie-off rings.

General Specifications:

Rated Capacity (<i>working load</i>)	310 lbs. (141 Kgs.)
Max. Allowed Arresting Force (M.A.F.) rating for retractable Devices or shock absorbers	900 lbs. (4 KN.)
Proof Load	
Anchor point eye	2250 lbs. (10 KN.) @ 45°
Proof Tests	UCT-353, 354, 355, 356, 375
Weight	4.5 lbs. (2.1 Kgs.)

Materials & Construction:

General Construction	Machined Aluminum
Tubular Components	6061-T6 Aluminum
Anchor Point Eye	Mild Steel, CS-500 Zinc Plated
Finish	Powder Coat
Plating Specifications	ASTM B-633 Type II SC2, CS-500 Leachant/Sealant Process

Application Restrictions:

1. This extension is to be used with the MILLER DURAHOIST Portable Fall-Arrest System Anchor Post **ONLY**.
2. The Extension may be used to anchor (1) worker **ONLY**.
3. Installed Anchor Post and accessories **MUST BE** 72" (1830mm) or less from any edge where a fall may occur.
4. Use of the extension derates the portable fall-arrest anchor post assembly to a maximum of TWO(2) workers tied off to the swivel tie-off head.
5. Portable fall-arrest system anchor post **MUST BE** in a vertical position any time it is being used as a fall-arrest anchor point.
6. Retractable devices and shock absorbers **MUST HAVE** a maximum arrest force (M.A.F.) rating of 900 lbs. (4 KN.) or less, and **MUST BE** installed and used in accordance with the manufacturer's instructions.
7. Each installation **MUST BE** approved to local standards by a qualified engineer.

CERTIFICATION

